




Hard Shell



FLOATATION VEST – NEPTUNE I



Hard Shell



OVERVIEW

The Neptune I model offers a tactical ballistic protection solution for users working on or around the water. It was designed keeping in mind the maritime security personnel or naval users, who require maximum protection with the flexibility of a standard tactical vest. Utilizing the BALCS cut style of soft armour, providing front, back and side protection; the Neptune I vest also has a detachable floatation collar with manual and automatic inflation. The Neptune I will provide the water based operator peace of mind while operating on vessels in hostile waters.



Hard Shell

OPTIONAL ACCESSORIES

SIZES

BP Vest bag/carrier
Hard Armor Panel

Small
Medium
Large

X Large
XX Large

FEATURES

Custom cut NIJ 0101.06 Level IIIA soft armour
Comfortable Padding Front / Back and Shoulders
Allowance for 10" by 12" Hard Armour Panels of Level III, Level III+ & Level IV. (fitted is HAP Pockets)
Allowance for Kevlar® Material inserts to be used in conjunction with (ICW) hard armour plates
Front to back wrap around ballistic protection
Adjustable side closure design

4 size adjustment straps
Externally and Internally adjustable waist bands to secure the vest to the wearer
Detachable Floatation Collar, Inflation time, less than 5 seconds
Minimum 24 hours floatation duration, 150N Buoyancy each from both the CO2 cylinders.
Available in PU coated hardwearing Nylon fabric, Cordura, Cotton fabric or as per customer's requirement and in a range of colors.

PROTECTION LEVEL


PERFORMANCE

Soft armour panel protects as per NIJ Level IIIA.
Can be upgraded to NIJ LEVEL III, III+, IV, depending upon the hard armour panel used.

Washable outer cover
Transfer soft armour protection from one carrier to another.

Specification for Floatation Device

1. Inflation time \leq 5secs
2. Floatation Duration \geq 24 hours
3. Buoyancy \geq 150N x 2
4. Buoyancy loss after 24 hours \leq 5%
5. CO2 Weight: 33grams x 2
6. Ambient temperature for use : -30oC to +65oC



Hard Shell






Hard Shell

WARRANTY

- 10 years performance warranty on hard armour panel
 - 5 years performance warranty on soft armour panel
 - 1 year performance warranty on Outer Carrier
 - 1 year for the floatation device.
- (Subject to usage conditions)



Hard Shell

